

Shoreline 汐岸

ANKER



产品技术参数

结构	簇绒高低圈	
标准纤维	100% 环球抗污尼龙	
染色方式	100% 原液染纱	
底背	Unit Back® (PVC & Bitumen Free) Unit Back Pro® (PVC & Bitumen Free)	
绒高 产品尺寸	英制	公制
	0.17 in	4.5mm±0.5mm
	9.84 X 39.37in	25cm X 100cm
	19.69 X 39.37in	50cm X 100cm
针密	12 in	49 / 10cm
针距	1/12 in	47.2 / 10cm
绒重	18 oz/yd ²	610 g/m ²
总厚度	0.24 in	6±0.5 mm
	0.31 in	8±0.5mm

功能特性

耐磨等级	33-LC1	
六足滚轮	ISO 10361	12000 转≥3.5
人流量等级	重度商业使用空间	

性能指标

隔音性	ISO 10140	ca. 23dB
吸音性	ISO 354	$\alpha_w=0.25$
热阻性	ISO 8302	ca. 0.07
阻燃性	DIN EN 13501-1	Cfl-s1
抗静电	ISO 6356	≤2.0 kV
耐光色牢度	ISO 105 B02	≥6
耐水色牢度	ISO 105 E01	≥4
干湿摩擦色牢度	ISO 105 X12	≥3-4
稳定性拔出力	ISO 4919	≥30N

环保认证

GUT	TVOC≤100µg/m ³
Declare Label	
EPD	

质保

15年耐磨有限保证
终身抗静电有限保证
终身抗褪色有限保证


证书




Declare.



铺装方式



工字铺



顺铺